


Product information

M12 Single Ended Cordsets - Shieldable Types - RKTS 4-288/5 M

Industrial Connecting Solutions:Circular Connectors:M8 - M12 Connectors:M12 Connectors:M12 Circular connector acc. to IEC 61076-2-101:Overmolded Single Ended M12 Cordsets:M12 Single Ended

Cordsets - Shieldable Types

http://www.e-catalog.beldensolutions.com/link/57078-24228-256281-256292-256304-58429-58479-74828/en/RKGTS_04-288-05/ulstate


Name		M12 Single Ended Cordsets - Shieldable Types
		
		Actuator/sensor cordset, single-ended, M12 female connector, 360° shielding connected to knurled nut, straight version, with threaded joint and molded cable, 4 poles, PUR jacket, halogen-free, screened, black, 5 meters
Delivery informations		
Availability		available
Product description		
Type		RKTS 4-288/5 M
Order No.		49205
Description		Actuator/sensor cordset, single-ended, M12 female connector, 360° shielding connected to knurled nut, straight version, with threaded joint and molded cable, 4 poles, PUR jacket, halogen-free, screened, black, 5 meters
Number of contacts		4
Color of housing		orange
Product characteristics		Vibration resistance, Oil resistance, Drag chains suitable
Classification		
Belden brand		Lumberg-Automation
Eclass-ID		27260702
Mechanical data		
Type of plug-in contact		Female connector
Design of housing		straight
Thread		M12
Design of electrical connection		connector M12
Coding of the M12 round plug connector		A
LED display present		✗
Environmental conditions		
Environmental temperature		-25 °C ... 80 °C
Degree of protection (IP), mounted		IP67
Pollution degree		3
Materials		
Housing material / Molded body		TPU
Contact bearer material		TPU
Contact material		CuZn
Contact material - Surface refinement		pre-nickel and 0.8 microns gold-plated
Knurled screw / nut material		CuZn, tined
Sealing material		FKM
Electrical data		
Contact resistance		≤ 5 mΩ
Rated current I _n		4 A at 40°C, UL and notice derating
Nominal voltage		240 V AC/DC
Rated voltage		250 V
Test voltage		2.0 kV eff./60 s
Insulation resistance		> 1 GΩ
Approvals		
Approvals		UL

Industrial Connecting Solutions: Circular Connectors: M8 - M12 Connectors: M12 Connectors: M12 Circular connector acc. to IEC 61076-2-101: Overmolded Single Ended M12 Cordsets: M12 Single Ended Cordsets - Shieldable Types

http://www.e-catalog.beldensolutions.com/link/57078-24228-256281-256292-256304-58429-58479-74828/en/RKGTS_04-288-05/uistate

Picture

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.