


The information/details in this datasheet merely contain general descriptions or performance factors which, when applied in an actual situation, do not always correspond with the described form, and may be amended by way of the further development of products. The desired performance factors shall only be binding if these are expressly agreed on conclusion of the contract.



Product description

Description	Actuator/sensor cordset with M12 female and male connector
Type	ASB 2-RST 4-265/0,2-RKT 8-362/5 P99

Technical data

Rated voltage	30 V
Rated current *	2 A at 40°C
Rated impulse voltage	0,8 kV
Pollution degree	3
Insulation resistance	> 10 ⁹ Ohm

* Notice derating

Materials

Contact	CuZn
Contact plating	Ni/Au
Contact bearer	TPU
Housing	TPU
over molding	TPU
Gasket(s)	FKM
Knurled nut	CuZn, nickel-plated
Hexagon nut	CuZn, nickel-plated
Knurled screw	CuZn, nickel-plated

Environmental conditions


Temperature range	-25 °C / +80 °C
-------------------	-----------------

* only if mounted and locked in combination with Hirschmann / Lumberg connector.

Cutline

Do not connect / disconnect under load.

* a : O-Ring



Standard products

Artikel-No.	Type
000-077-088	ASB 2-RST 4-265/0,2-RKT 8-362/2 P99