


Product information

M12 Receptacle connector, front mounting, with stranded wire - RKFM 5/0,5 M

Industrial Connecting Solutions: Circular Connectors: M8 - M12 Connectors: M12 Connectors: M12 Circular connector acc. to IEC 61076-2-101: M12 Receptacle Connectors: M12 Receptacle connector, front mounting, with stranded wire

<https://www.e-catalog.beldensolutions.com:443/link/57078-24228-256281-256292-256304-58429-58480-76078/en/RKG-05-xM-16/uistate>

Name	
M12 Receptacle connector, front mounting, with stranded wire	
	
Receptacle connector, for front mounting, M12 female connector, assembled stranded wire, solder contacts potted with epoxy, 5 poles, A coding, chassis side thread M16 x 1.5 (panel nut RSKFM 16).	
Delivery informations	
Availability	available
Product description	
Type	RKFM 5/0,5 M
Order No.	26132
Description	Receptacle connector, for front mounting, M12 female connector, assembled stranded wire, solder contacts potted with epoxy, 5 poles, A coding, chassis side thread M16 x 1.5 (panel nut RSKFM 16).
Number of contacts	5
Color of housing	silver
Product characteristics	Oil resistance
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Female connector
Design of housing	straight
Thread	M12
Design of electrical connection	stranded wire
Coding of the M12 round plug connector	A
LED display present	✗
Environmental conditions	
Environmental temperature	-25 °C ... 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	CuZn, nickel-plated
Contact material	CuSn
Contact material - Surface refinement	pre-nickeled and 0.3 microns gold-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current I _n	4 A at 40°C, UL and notice derating
Nominal voltage	60 V
Rated voltage	63 V
Test voltage	1.5 kV eff./60 s
Insulation resistance	> 1 GΩ
Approvals	
Approvals	UL

Belden Deutschland GmbH

Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect.
The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.