



RoHS 

	A-Coding	B-Coding
Pin 1	brown	brown
Pin 2	white	green
Pin 3	blue	blue
Pin 4	black	red
Pin 5	grey	grey



Order No.	Type	Coding	Number of contacts	colour contact bearer
934-449-001	EM12M4 FIX	A	4	black
934-449-002	EM12M4FIX 500 Au	A	4	black
934-449-201	EM12M5FIX Au	A	5	black
934-449-211	EM12M5B FIX	B	5	grey

The information/details in this datasheet merely contain general descriptions or performance factors which, when applied in an actual situation, do not always correspond with the described form, and may be amended by way of the further development of products. The desired performance factors shall only be binding if these are expressly agreed on conclusion of the contract.



**Product description**

Description	appliance plug, screw-in assembly
Type	EM12M..., see standard products
Order No	934-449-..., see standard products
Type of contacts	male
Number of contacts	see standard products
Standard	IEC 61076-2-101 D
Construction type	GM
Color housing	silver

**Technical data**

Rated voltage	60V AC/DC, 5-poles 250 V AC/DC, 4-poles
Rated current *	4 A ; notice derating
Rated impulse voltage	1,5 kV, 5-poles 2,5 kV, 4-poles
Pollution degree	3
Contact resistance	< 10 mOhm
Type of connection	solder
Mounting	M16x1,5

**Materials**

Contact	CuZn
Contact plating	Cu/Au
Contact bearer	PA 6 GF
Housing	CuZn
Gasket(s)	Viton
Wire	see cable-data

**Environmental conditions**

Protection class (IEC 60529) *	IP67, IP68 (24h, 1m) *
Temperature range (connector)	-25°C to +90°C, notice derating
Temperature range (cable, hard-wired)	-25°C to +105°C
Temperature range (gasket)	-25°C to +190°C

\* only if mounted and locked in combination with Hirschmann / Lumberg connector.

**Flammability class**

Contact bearer	UL 94 V-2
----------------	-----------

**Accessories**


Accessories to order separately	Locking nut M16x1,5: 735-413-002
---------------------------------	----------------------------------

**Cable-data**

Cabletype	single wires
Wire length L	see standard products
Cable size	0,34 mm <sup>2</sup>
Wire-colors, pin-assignment	see page 1
Wire isolation	PVC, UL-Style 1007-1569
Wire stranding	7x0,25 mm

## Cutline

Do not connect or disconnect under load.



#### Standard products

Artikel-No.	Type
934-449-001	EM12M4A FIX
934-449-002	EM12M4 FIX 500 Au
934-449-201	EM12M5A FIX
934-449-211	EM12M5B FIX